

# PAR38-5CCT

## Selectable LED PAR38 Light Bulb



Project	
Type	
Location	

<b>Application</b>	Interior and exterior. Under soffit.
<b>Environment</b>	Dry, damp, and wet locations. Rated for use in enclosed fixtures.
<b>Material</b>	Alumimun and PC
<b>Dimmable</b>	Yes, 100%-10%. TRIAC dimming
<b>Finish</b>	White
<b>Dimension</b>	Dia 4-7/8" x H 5-1/8"
<b>Input Voltage</b>	120V AC, 60Hz
<b>Wattage</b>	15W
<b>Color Temperature</b>	5CCT selectable – 2700K-3000K-3500K-4000K-5000K
<b>Lumen</b>	1000-1100 Lm
<b>Beam Angle</b>	40°
<b>CRI</b>	> 90
<b>IP Rating</b>	IP44
<b>Operating Temperature</b>	-25°C~40°C (-13°F~104°F)
<b>Base</b>	E26
<b>Certification</b>	cETLus
<b>Warranty</b>	2-Year Limited Warranty. Estimated 25,000 Hours Useful Life of LED



CCT Selectable



Dimmable



Wet Location



### ORDERING INFORMATION

Model#	Wattage	CCT
PAR38	15W	5CCT
PAR38	15W 15W – 1100Lm	5CCT 5 CCT Selectable

### DIMENSIONS

