

PUK-M2

LED Puck Light



Project	
Type	
Location	

Application	Interior. Under Cabinet.
Environment	Dry and Damp Locations
Material	Aluminum Trim with Frosted Acrylic Diffuser
Dimmable	100%-10%. TRIAC Dimming
Finish	White / Black / Silver
Hole Cut	Ø 1-3/4" (44.5mm)
Input Voltage	12V DC, 50/60Hz
Wattage	2W
Color Temperature	3000K / 4000K / 5000K
Lumen	160 Lm
Beam Angle	120°
CRI	> 80
Dimensions	Ø 2" x H 1/2" (Ø 50mm x H 12mm)
IP Rating	42
Operating Temperature	-10°C~40°C (14°F~104°F)
Mounting	Recessed Mount
Certification	cETLus
Warranty	5-Year Limited Warranty. Estimated 25,000 Hours Useful Life of LED



Dimmable



Damp Location



ORDERING GUIDE

Model#	Size	Wattage	CCT	Finish	Driver Options (Sold Separately)
PUK-M2	2	2			
PUK-M2	2 2inch	2 2W – 160Lm	30K 3000K	WH White	TFH-12024 12V 24W for Max. 9 units
			40K 4000K	BK Black	TFH-12060 12V 60W for Max. 24 units
			50K 5000K	SV Silver	

DIMENSIONS

